

CASE STUDY 1



PRODUCT:	AIR COOLED HEAT EXCHANGER
CUSTOMER:	KESKINOGLU
SPECIFICATIONS:	W : 2140 mm L: 6000 mm Extruded Tube with aluminum fin Tube : \varnothing 26,9*2,6 mm (1.4401) Quantity of Tube: 624 mt Steam inlet temp. : 143,6 °C Steam outlet temp.: 141 °C Steam inlet pressure : 4 Bar Air inlet temp. : 33 °C Air outlet temp. : 52,45 °C Air flow rate: 88,2 m ³ /s

CASE STUDY 1 PHOTOS



CASE STUDY 2



PRODUCT: AIR COOLED HEAT EXCHANGER
CUSTOMER: PETKIM
SPECIFICATIONS: New bundle replacement
Extruded tube: Steel tube with aluminum fin
Quantities of tube : 5250 m
Tube diameter : 26,9*2,6 mm

CASE STUDY 2 PHOTOS



CASE STUDY 3



PRODUCT:	HEATER COILS
APPLICATION:	DRYING CACAO WITH HOT AIR
CUSTOMER:	ÜLKER ÖNEM GIDA
SPECIFICATIONS:	Saturated Steam Inlet temperature: 188,1 °C Saturated Steam Outlet temperature: 187,9 °C Saturated Steam Inlet pressure: 12 bar Air inlet temperature: 30 °C Air outlet temperature: 150 °C The elliptical steel tube with rectangular fin Bare tube long: 34 mm Short: 14 mm Fin size: 55*26*0,4 mm

CASE STUDY 4



PRODUCT:	FINAL HEATER
CUSTOMER:	ASOS
SPECIFICATIONS:	Water inlet temp. : 90 °C Water outlet temp.: 70 °C Water inlet pressure : 4 Bar Air inlet temp. : 54 °C Air outlet temp. : 73,93 °C Stainless steel tube with stainless fin

CASE STUDY 4 PHOTOS





**COPPER TUBE WITH ALUIMINUM FİN FOR
DRY COOLER APPLICATIONS**



Fabrika: Hacı Şeremet Mevkii Velimeşe – ERGENE/Tekirdağ/TÜRKİYE
Web: www.konukisi.com E - Mail: info@konukisi.com Tel: +90 282 676 48 90 Faks: +90 282 676 48 98

